

Beweging, Temperatuur Clock en Buttons

Same setup but improved with three buttons to make it completely indepedend from PC.

```
#include <Wire.h>
#include <LiquidCrystal_I2C.h>
#include <DHT.h>
#include <DS3231.h>

// --- Definitions ---
#define DHTPIN 4      // Pin connected to the DHT11 data pin
#define DHTTYPE DHT11 // Specify DHT11 sensor
#define BUTTON1PIN 8
#define BUTTON2PIN 9
#define BUTTON3PIN 10
#define TREND_DISPLAY_DURATION_MS 600000 // 10 minutes, time to keep the sinal (arrow up/down) in display
#define HISTORICAL_DATA_ENTRIES_COUNT 5 // Define the length of the history (min-max) buffers: so we keep
the last N hours of min max data.
#define MAX_HISTORY_STRING_LENGTH 100 // Maximum characters for the history string
#define DEBUG true           // Set to true to enable debug printing, false to disable

DHT dht(DHTPIN, DHTTYPE);

DS3231 myRTC;
bool century = false;
bool h12Flag;
bool pmFlag;

int count = 0;
int pirPin = 12; // Pin for the HC-S501 sensor
int pirValue;

LiquidCrystal_I2C lcd = LiquidCrystal_I2C(0x27, 16, 2);
unsigned long previousMillis = 0;
```

```
const long dhtInterval = 2000; // Interval for DHT readings

// Custom characters for the LCD arrows
byte downChar[] = {
    B00000,
    B00000,
    B00100,
    B00100,
    B00100,
    B10101,
    B01110,
    B00100
};

byte upChar[] = {
    B00100,
    B01110,
    B10101,
    B00100,
    B00100,
    B00100,
    B00000,
    B00000
};

byte degreeChar[] = {
    B00110,
    B01001,
    B01001,
    B00110,
    B00000,
    B00000,
    B00000,
    B00000
};

byte maxChar[] = {
    B01110,
    B00000,
    B00100,
```

```

B01110,
B10101,
B00100,
B00100,
B00100
};

byte minChar[] = {
    B00100,
    B00100,
    B00100,
    B10101,
    B01110,
    B00100,
    B00000,
    B01110
};

//-----
// Generic MeasurementSensor Class Template
//-----

template<typename T>
class MeasurementSensor {
public:
    // Constructor: initializes with an initial measurement value and history capacity N.
    MeasurementSensor(long sigInterval)
        : measurement(0),
        arrow(0),
        arrowMillis(0),
        lowestMeasurement(0),
        highestMeasurement(0),
        signalInterval(sigInterval),
        historyCount(0),
        historyIndex(0) {}

    // Destructor (no longer needed due to no dynamic memory)
    //~MeasurementSensor() {}

    // Update the measurement reading and determine the arrow indicator.
    void update(T newMeasurement, unsigned long currentMillis) {

```

```

// For the first valid measurement, initialize min/max if needed.

if (lowestMeasurement == static_cast<T>(0) && highestMeasurement == static_cast<T>(0)) {
    lowestMeasurement = newMeasurement;
    highestMeasurement = newMeasurement;
}

// Update the current interval's min and max.

if (newMeasurement < lowestMeasurement) {
    lowestMeasurement = newMeasurement;
}

if (newMeasurement > highestMeasurement) {
    highestMeasurement = newMeasurement;
}

// Determine arrow indicator logic.

if (newMeasurement == measurement && currentMillis - arrowMillis >= signalInterval) {
    arrow = 0;
} else {
    if (newMeasurement < measurement) {
        arrow = 1; // Down arrow
        arrowMillis = currentMillis;
    }

    if (newMeasurement > measurement) {
        arrow = 2; // Up arrow
        arrowMillis = currentMillis;
    }

    if (lowestMeasurement != highestMeasurement) {
        if (newMeasurement == this->getLowest()) {
            arrow = 4; // Indicator for lowest measurement
            arrowMillis = currentMillis;
        }

        if (newMeasurement == this->getHighest()) {
            arrow = 5; // Indicator for highest measurement
            arrowMillis = currentMillis;
        }
    }
}

// Reset arrow if previous value was an invalid initial value.

if (measurement == static_cast<T>(0)) {

```

```
    arrow = 0;
}

measurement = newMeasurement;
}

// Getters for measurement and arrow.

T getMeasurement() const {
    return measurement;
}

// Returns the lowest measurement seen over the history combined with the current interval.

T getLowest() const {
    T minVal = lowestMeasurement;
    // Loop over the history array.
    for (size_t i = 0; i < historyCount; i++) {
        if (lowestHistory[i] < minVal) {
            minVal = lowestHistory[i];
        }
    }
    return minVal;
}

// Returns the highest measurement seen over the history combined with the current interval.

T getHighest() const {
    T maxVal = highestMeasurement;
    // Loop over the history array.
    for (size_t i = 0; i < historyCount; i++) {
        if (highestHistory[i] > maxVal) {
            maxVal = highestHistory[i];
        }
    }
    return maxVal;
}

int getArrow() const {
    return arrow;
}

// Reset the min and max values.
```

```

// The current lowest and highest measurements are stored in the history arrays.

void resetMinMax(T newMeasurement) {
    // Store the current min and max in the arrays at the current history index.
    lowestHistory[historyIndex] = lowestMeasurement;
    highestHistory[historyIndex] = highestMeasurement;

    lowestMeasurement = newMeasurement;
    highestMeasurement = newMeasurement;

    // Increment historyIndex as a circular buffer.
    historyIndex = (historyIndex + 1) % HISTORICAL_DATA_ENTRIES_COUNT;
    if (historyCount < HISTORICAL_DATA_ENTRIES_COUNT) {
        historyCount++;
    }
}

void getHistoryString(bool useHighest, char* buffer, size_t bufferSize) const {
    // Initialize the buffer to an empty string.
    buffer[0] = '\0';

    // Determine the index of the oldest element.
    size_t oldestIndex = (historyCount < HISTORICAL_DATA_ENTRIES_COUNT) ? 0 : historyIndex;

    // Loop over the valid history entries in order.
    for (size_t i = 0; i < historyCount; i++) {
        size_t index = (oldestIndex + i) % HISTORICAL_DATA_ENTRIES_COUNT;
        T value = useHighest ? highestHistory[index] : lowestHistory[index];

        // Temporary buffer for the converted float value.
        char tempValue[10];
        // Convert the float value to a string with width 4 and one decimal point.
        dtostrf(static_cast<double>(value), 4, 1, tempValue);

        // Check if adding the next value will overflow the main buffer.
        size_t remainingSpace = bufferSize - strlen(buffer) - 1;
        size_t charsNeeded = strlen(tempValue) + (i < historyCount - 1 ? 2 : 0); // value + ", "
        if (charsNeeded > remainingSpace) {
            Serial.println("Error: Insufficient buffer space in getHistoryString!");
            return; // You may choose to handle this differently.
        }

        // Append the value to the buffer.
        strcpy(buffer + strlen(buffer), tempValue);
    }
}

```

```
    }

    // Concatenate the value to the buffer.
    strcat(buffer, tempValue);

    // Add the separator if it's not the last element.
    if (i < historyCount - 1) {
        strcat(buffer, ", ");
    }
}
```

private:

```
    T measurement;
    int arrow;
    unsigned long arrowMillis;
    T lowestMeasurement;
    T highestMeasurement;
    long signalInterval;

    // History storage: fixed size arrays
    T lowestHistory[HISTORICAL_DATA_ENTRIES_COUNT];
    T highestHistory[HISTORICAL_DATA_ENTRIES_COUNT];
    size_t historyCount;
    size_t historyIndex;
};
```

```
class Button {

private:
    int pin;
    int prevState;
    const char* name;
    unsigned long pressStartTime;
    bool longPressTriggered;
    const unsigned long LONG_PRESS_DURATION = 1000; // 1 second for long press

public:
```

```
// Constructor: initialize the button pin and its name
Button(int pin, const char* name)
: pin(pin), prevState(LOW), name(name), pressStartTime(0), longPressTriggered(false) {
pinMode(pin, INPUT);
}

// Update the button state and return true if the button was pressed (transition from LOW to HIGH)
bool update() {
int currentState = digitalRead(pin);
bool pressed = false;

if (currentState != prevState) {
// Button state changed
if (currentState == HIGH) {
// Button was just pressed
pressStartTime = millis();
longPressTriggered = false;
} else {
// Button was just released
if ((millis() - pressStartTime < LONG_PRESS_DURATION) && !longPressTriggered) {
// Short press detected
pressed = true;
}
pressStartTime = 0;
}
prevState = currentState;
}

return pressed;
}

// Check for long press and return true if long press is detected
bool checkLongPress() {
int currentState = digitalRead(pin);

if (currentState == HIGH && prevState == HIGH) {
// Button is being held down
if (millis() - pressStartTime > LONG_PRESS_DURATION && !longPressTriggered) {
longPressTriggered = true;
return true;
}
}
}
```

```

    }

}

return false;
}

// Getter for the button's name
const char* getName() {
    return name;
}

};

class DateTimeSettings {
private:
    // RTC reference
    DS3231& rtc;

    // LCD reference
    LiquidCrystal_I2C& lcd;

    // Setting state variables
    bool isActive;
    int settingIndex; // 0=day, 1=month, 2=hour, 3=minute
    int currentDay, currentMonth, currentHour, currentMinute;

    // Blinking effect variables
    unsigned long lastBlinkTime;
    const unsigned long BLINK_INTERVAL = 500; // 500ms blink interval
    bool showField;

    // Reference to century flag needed for RTC
    bool& centuryFlag;
    bool h12Flag, pmFlag; // RTC flags

public:
    // Constructor
    DateTimeSettings(DS3231& rtcInstance, LiquidCrystal_I2C& lcdInstance, bool& century)
        : rtc(rtcInstance),
        lcd(lcdInstance),
        isActive(false),

```

```
settingIndex(0),
lastBlinkTime(0),
showField(true),
centuryFlag(century),
h12Flag(false),
pmFlag(false) {

}

// Start the settings mode
void start() {
    isActive = true;
    settingIndex = 0; // Start with day

    // Get current values from RTC
    currentDay = rtc.getDate();
    currentMonth = rtc.getMonth(centuryFlag);
    currentHour = rtc.getHour(h12Flag, pmFlag);
    currentMinute = rtc.getMinute();

    showField = true;
    lastBlinkTime = millis();

    displaySettings();
}

// Check if settings mode is active
bool isSettingActive() const {
    return isActive;
}

// Exit settings mode
void exit() {
    isActive = false;
    lcd.clear();
}

// Move to the next field
void nextField() {
    settingIndex++;
    showField = true; // Reset blink state
```

```
if (settingIndex > 3) {  
    // All fields set, save the time  
    rtc.setDate(currentDay);  
    rtc.setMonth(currentMonth);  
    rtc.setHour(currentHour);  
    rtc.setMinute(currentMinute);  
    rtc.setSecond(0); // Reset seconds to 00  
  
    // Exit setting mode  
    exit();  
    return;  
}  
  
displaySettings();  
}  
  
// Increase the current field value  
void increaseValue() {  
    switch (settingIndex) {  
        case 0: // Day  
            currentDay++;  
            if (currentDay > 31) currentDay = 1;  
            break;  
        case 1: // Month  
            currentMonth++;  
            if (currentMonth > 12) currentMonth = 1;  
            break;  
        case 2: // Hour  
            currentHour++;  
            if (currentHour > 23) currentHour = 0;  
            break;  
        case 3: // Minute  
            currentMinute++;  
            if (currentMinute > 59) currentMinute = 0;  
            break;  
    }  
    showField = true; // Reset blink state  
    displaySettings();  
}
```

```

// Decrease the current field value
void decreaseValue() {
    switch (settingIndex) {
        case 0: // Day
            currentDay--;
            if (currentDay < 1) currentDay = 31;
            break;
        case 1: // Month
            currentMonth--;
            if (currentMonth < 1) currentMonth = 12;
            break;
        case 2: // Hour
            currentHour--;
            if (currentHour < 0) currentHour = 23;
            break;
        case 3: // Minute
            currentMinute--;
            if (currentMinute < 0) currentMinute = 59;
            break;
    }
    showField = true; // Reset blink state
    displaySettings();
}

// Update method to be called in the main loop
void update() {
    // Return if not in setting mode
    if (!isActive) return;

    // Handle blinking effect
    if (millis() - lastBlinkTime >= BLINK_INTERVAL) {
        lastBlinkTime = millis();
        showField = !showField;
        displaySettings();
    }
}

private:
    // Display the settings screen

```

```
void displaySettings() {
    lcd.clear();
    lcd.setCursor(0, 0);
    lcd.print("Set Date & Time");

    lcd.setCursor(1, 1);

    // Display day - blinking when being set
    if (settingIndex != 0 || showField) {
        print2digits(currentDay);
    } else {
        lcd.print(" ");
    }

    lcd.print("-");

    // Display month - blinking when being set
    if (settingIndex != 1 || showField) {
        print2digits(currentMonth);
    } else {
        lcd.print(" ");
    }

    lcd.setCursor(8, 1);

    // Display hour - blinking when being set
    if (settingIndex != 2 || showField) {
        print2digits(currentHour);
    } else {
        lcd.print(" ");
    }

    lcd.print(":");

    // Display minute - blinking when being set
    if (settingIndex != 3 || showField) {
        print2digits(currentMinute);
    } else {
        lcd.print(" ");
    }
}
```

```
}

// Helper function to print 2 digits with leading zero
void print2digits(int number) {
    if (number < 10) {
        lcd.print("0");
    }
    lcd.print(number, DEC);
}
};

//-----
// Global Instances for Temperature and Humidity
//-----
MeasurementSensor<float> tempSensor(TREND_DISPLAY_DURATION_MS);
MeasurementSensor<int> humiditySensor(TREND_DISPLAY_DURATION_MS);

void setup() {
    Serial.begin(9600);
    dht.begin();
    delay(2000);

    lcd.init();
    lcd.backlight();
    lcd.clear();
    lcd.createChar(1, downChar);
    lcd.createChar(2, upChar);
    lcd.createChar(3, degreeChar);
    lcd.createChar(4, minChar);
    lcd.createChar(5, maxChar);

    pinMode(pirPin, INPUT);

    pinMode(BUTTON1PIN, INPUT);
    pinMode(BUTTON2PIN, INPUT);
    pinMode(BUTTON3PIN, INPUT);

    // myRTC.setYear(2025);
    // myRTC.setMonth(3);
```

```

// myRTC.setDate(20);
// myRTC.setHour(10);
// myRTC.setMinute(49);
// myRTC.setSecond(0);
}

void print2digits(int number) {
if (number < 10) {
  lcd.print("0");
}
lcd.print(number, DEC);
}

int lastResetHour = -1; // Initialize to an invalid hour

// Create instances for each button
Button button1(BUTTON1PIN, "Button 1");
Button button2(BUTTON2PIN, "Button 2");
Button button3(BUTTON3PIN, "Button 3");

int displayModus = 1; // we want temp range when 2 we want humidity range

// Add this near the top of your code, with your other global instances
DateTimeSettings dateTimeSettings(myRTC, lcd, century);

void loop() {
delay(20);

// Check if we are in setting mode
if (dateTimeSettings.isSettingActive()) {
  dateTimeSettings.update();

// Check for long press on button 1 to exit setting mode
  if (button1.checkLongPress()) {
    dateTimeSettings.exit();
    return;
  }

// Handle button 1 (short press - move to next field)

```

```
if (button1.update()) {  
    dateTImeSettings.nextField();  
}  
  
// Handle button 2 (decrease value)  
if (button2.update()) {  
    dateTImeSettings.decreaseValue();  
}  
  
// Handle button 3 (increase value)  
if (button3.update()) {  
    dateTImeSettings.increaseValue();  
}  
  
return; // Skip the normal loop when in setting mode  
}  
  
// Check for long press on button 1 to enter setting mode  
if (button1.checkLongPress()) {  
    dateTImeSettings.start();  
    return;  
}  
  
// The rest of your existing loop code stays the same  
// Update each button and print if pressed  
if (button1.update()) {  
    Serial.print(button1.getName());  
    Serial.println(" pressed");  
}  
if (button2.update()) {  
    Serial.print(button2.getName());  
    Serial.println(" pressed");  
    count = 5;  
    previousMillis = 0;  
    displayModus = 1;  
}  
if (button3.update()) {  
    Serial.print(button3.getName());  
    Serial.println(" pressed");  
    count = 5;
```

```
previousMillis = 0;
displayModus = 2;
}

// Check for movement
pirValue = digitalRead(pirPin);
// Serial.println(pirValue);

if (pirValue) {
    lcd.backlight();
}

// Do we need to update the display?
unsigned long currentMillis = millis();
if (currentMillis - previousMillis >= dhtInterval) {
    previousMillis = currentMillis;

    if (!pirValue) {
        lcd.noBacklight();
    }

    count++;

    // Read new values from the DHT sensor
    float newTemperature = dht.readTemperature();
    int newHumidity = dht.readHumidity();

    if (isnan(newTemperature) || isnan(newHumidity)) {
        Serial.println("Failed to read from DHT sensor!");
        lcd.clear();
        lcd.print(" *** DHT Error *** ");
        delay(5000);
        return; // next iteration in the loop
    }

    // Update our measurement sensors
    tempSensor.update(newTemperature, currentMillis);
    humiditySensor.update(newHumidity, currentMillis);

    // Get current hour from RTC
}
```

```

int currentHour = myRTC.getHour(h12Flag, pmFlag);
// Check if hour has changed
if (currentHour != lastResetHour) { // || count%10==0

    tempSensor.resetMinMax(newTemperature);
    humiditySensor.resetMinMax(newHumidity);

    lastResetHour = currentHour;
}

Serial.println(count);
char tempHistoryBuffer[MAX_HISTORY_STRING_LENGTH];
tempSensor.getHistoryString(false, tempHistoryBuffer, sizeof(tempHistoryBuffer));
Serial.print("min temp history: ");
Serial.println(tempHistoryBuffer);

char tempHistoryBuffer2[MAX_HISTORY_STRING_LENGTH];
tempSensor.getHistoryString(true, tempHistoryBuffer2, sizeof(tempHistoryBuffer2));
Serial.print("max temp history: ");
Serial.println(tempHistoryBuffer2);

Serial.println();

// Update the LCD display for temperature
lcd.setCursor(0, 0);
if (!(count % 6) && displayModus == 1) {
    lcd.print("");
    lcd.print(tempSensor.getLowest(), 1);
    lcd.write(3);
    lcd.print(" ");
    lcd.print(tempSensor.getHighest(), 1);
    lcd.write(3);
    lcd.print(" ");
} else {
    if (tempSensor.getArrow()) {
        lcd.write(tempSensor.getArrow());
    } else {
        lcd.print(" ");
    }
}

```

```

lcd.print(tempSensor.getMeasurement(), 1);
lcd.write(3); // degree symbol
lcd.print("C  ");
}

// Update the LCD display for humidity
if (!(count % 6) && displayModus == 2) {
    lcd.setCursor(9, 0);
    lcd.print(humiditySensor.getLowest(), 1);
    lcd.print("% ");
    lcd.print(humiditySensor.getHighest(), 1);
    lcd.print("%");
} else {
    lcd.setCursor(12, 0);
    if (humiditySensor.getArrow()) {
        lcd.write(humiditySensor.getArrow());
    } else {
        lcd.print(" ");
    }
    lcd.print(humiditySensor.getMeasurement());
    lcd.print("%");
}

// Update the LCD display second row, date
lcd.setCursor(1, 1);
print2digits(myRTC.getDate());
lcd.print("-");
print2digits(myRTC.getMonth(century));

// Update the LCD display second row, time
lcd.setCursor(10, 1);
print2digits(myRTC.getHour(h12Flag, pmFlag));
lcd.print(":");
print2digits(myRTC.getMinute());
}
}

```

<https://www.circuito.io/app?components=97,97,97,514,10167,11022,417986,821989,931983>

Revision #2

Created 6 April 2025 15:12:11 by Max

Updated 6 April 2025 18:38:13 by Max