

Brand-Brothers

Documentatie web site Brand-Brothers

- [Forms](#)
- [Equipment](#)
- [Technical \(Equipment \)](#)
- [Fotobooth](#)
- [Sets and availabilty](#)

Forms

Handleiding

Deze handleiding beschrijft de verschillende parameters die je kunt gebruiken bij het configureren van een bier selectie formulier.

Het form wordt aangeroepen door middel van een URL en alle parameters worden in de URL meegegeven.

Voorbeeld:

```
https://...../brand-brothers/forms/?eigenaar=naam&merk=Texels&set=Texels-  
vuurtorenbar&minbeers=3&beerfilter=amstel&options=1,2,3,4,25,26&t=1&maxbeers=3
```

Spaties in URL

In de gehele URL moeten spaties worden gecodeerd als `%20`.

Parameters

De parameters zoals in het voorbeeld getoond, worden hieronder beschreven. Elke parameter is **rood** gemarkeerd.

minbeers

- **Beschrijving:** Het minimaal aantal bieren dat geselecteerd moet worden.
- **Werking:** Als er minder bieren zijn geselecteerd dan het minimum, krijg je een waarschuwing wanneer je probeert het formulier te versturen.

maxbeers

- **Beschrijving:** Het maximaal aantal bieren dat geselecteerd kan worden.
- **Werking:** Als je meer bieren selecteert dan het maximum, verschijnt er onmiddellijk een waarschuwing.

Verborgen Velden

- **Beschrijving:** De volgende velden zijn verborgen en kunnen via de URL worden meegegeven. De verborgen velden worden door het formulier meegestuurd en verschijnen in de email.
 - **eigenaar:** De eigenaar van het biermerk.
 - **merk:** De naam van het biermerk.
 - **set:** De naam van de set die in de titel van het formulier verschijnt.

t (Testmodus)

- **Beschrijving:** Hiermee kun je de testmodus van het formulier instellen. aan **t** kunnen de volgende waarden worden gegeven:
 - **0:** Normale werking (dezelfde als geen waarde opgegeven).
 - **1:** Alle verplichte velden zijn niet meer verplicht en het formulier wordt niet per e-mail verzonden.
 - **2:** Alle verplichte velden zijn niet meer verplicht en het formulier wordt wel per e-mail verzonden

options

- **Beschrijving:** Een lijst van opties die als een komma-gescheiden lijst moeten worden opgegeven. Deze opties worden getoond op het formulier.

beerfilter

- **Beschrijving:** Een filter om bieren op naam te selecteren.
- **Werking:** Als de waarde 'none' is, wordt de gehele bierselectie niet getoond. Je kunt meerdere filters specificeren, bijvoorbeeld: `beerfilter=amstel,brand`.

Options aanpassen

Om options aan te passen kan deze URL worden gebruikt:

```
https://...../.../brand-brothers/forms/options
```

of nieuwe interface

<https://...../.../brand-brothers/forms/options/index2.php>

Optienummer

Elke optie heeft een nummer. Aan de hand van dit nummer wordt de optie op het formulier geplaatst. De nummers hoeven niet uniek te zijn. Wanneer meerdere opties hetzelfde nummer hebben, worden alle opties op het formulier getoond wanneer deze optie wordt gekozen.

Optienaam

De naam van de optie is de naam die op de aanvraag verschijnt (email).

Optielabel

Het label is de de naam zoals die op het formulier verschijnt.

Extra naam

De extra naam is de (open) vraag die wordt gesteld indien de optie wordt geselecteerd. De naam is de naam zoals die op het aanvraag (email) verschijnt.

Extra label

Het extra label is de (open) vraag die wordt gesteld indien de optie wordt geselecteerd. Het label is de naam zoals die op het formulier verschijnt.

URL naar options (back-up)

De 'database' waarin de options worden opgeslagen kun je via de volgende URLs controleren:

<https://.../.../brand-brothers/forms/options/options.js>

<https://.../.../brand-brothers/forms/options/options.json>

Deze bestanden zou je ook als (extra) back-up kunnen gebruiken.

De twee bestanden bevatten dezelfde informatie, maar zijn om technische redenen op een andere wijze vormgegeven.

Options kunnen niet worden aangepast?

Als de opties niet kunnen worden aangepast, controleer dan de twee bestanden. Zijn de wijzigingen in deze bestanden wel aangepast dan zorgt de cache van de browser ervoor dat de wijzigingen niet (direct) worden getoond. Laadt de pagina dan opnieuw en **leeg de browser cache** (dit werkt op elke browser anders).

Beers aanpassen

(dit is nog nooit in productie getest)

```
https://...../brand-brothers/forms/beers
```

of nieuwe interface

```
https://...../brand-brothers/forms/beers/index2.php
```

Een beer heeft een ID en een naam zoals dat op het form te zien is. Zorg ervoor dat de ID's uniek blijven.

--

Equipment

Equipmentlist

(in ontwikkeling)

<https://....brand-brothers/equipment-list/folders.php>

--

Technical (Equipment)

Equipment

folder -> equipment ->

Performance

Plaatjes

Plaatjes staan in Amazon Cloud en zijn 200kb tot 500kb.

No Cache, no optimazation

Het laden van 5 items duurt 1 tot 2.5 seconden afhankelijk van de grootte van de plaatjes.

Async laden plaatjes

Laadtijden per 5 items tussen de 0.6 en 1.2 seconden zijn.

Plaatjes kleiner maken (optimized for web)

Het laden van 5 items duurt 2 ms.. 200 to 500 maal sneller.

API Call optimization

API calls naar rentman kosten gemiddeld 120 ms per call (dat is snel); voor elk item heb je wel 3 call nodig (item data, plaatje data, calender data).

Dat is dus 360 ms per item.

Via cache is dat < 1 ms.

Mogelijk optimalisatie is parrallel async verwerking.

Implementation

all getc api calls are cached. The cache has a predefiend TTL \$cache_ttl = 3600
the raw return value of the API is json encoded written to file.

There is code to delete all the cache (not tested yet)

Rerender plaatje sop server

Let op dat de GD library op de server actief moet zijn.

Amazon picture load

TLS Handshake and Connection Setup: 100 ms

s3-eu-west-1.amazonaws.com - ping time 27 ms

server processing - 10 ms

Network tranfer speed 0.8 sec/KB

Cache of rentman API

all getc api calls are cached. The cache has a predefiend TTL \$cache_ttl = 3600

the raw return value of the API is json encoded written to file.

There is code to delete all the cache (not tested yet)

Images cache

Images are cached as images (binaries) and are re-rendered at a lower resolution.

Images are cached under the name [equipment-id]-[image-modified].jpg

When equipment ids are not valid any more, there could be orphan images in the cache.

When the image is updated for an exisitng equipment id, there will be two files with the same equipment-id,

the one with the lowest image-modified timestamp can be deleted.

There is no code for this yet.

Performance test

- Orginele laadtijd: 5,4 seconden (1.8 MB plaatjes)
- Img cache v no cache 2600/3500 ms - 2 ms
- API call cache v no cache: 1700 ms - 2 ms
- na cache plaatjes/ api calls 2 ms

Rechten op directory (Ubuntu)

```
// create new group
sudo groupadd shared-www
```

```
// add users to group
```



```
sudo usermod -aG shared-www www-data
```

```
sudo usermod -aG shared-www max
```

```
// set shared group as owner
```

```
sudo chown -R :shared-www /path/to/shared-directory
```

```
sudo chmod -R 770 /path/to/shared-directory
```

```
// Ensure that any new files or directories created inside the shared directory inherit the group ownership of  
shared-group.
```

```
sudo chmod g+s /path/to/shared-directory
```

Fotobooth

Code voor Arduino

```
#include <Keyboard.h>

const int inputPin = 12; // Pin connected to Nayax output
int lastState = LOW;    // Previous state of the input pin
int count;

void setup() {
  pinMode(inputPin, INPUT);    // Set the pin as input
  digitalWrite(LED_BUILTIN, HIGH); // initialize digital pin LED_BUILTIN as an output.
  pinMode(LED_BUILTIN, OUTPUT); // turn the LED on (HIGH is the voltage level)
  Keyboard.begin();           // Initialize the keyboard emulation
  Serial.begin(9600);
  count = 0;
  delay(5000);                // Delay to give time to connect the Arduino
  digitalWrite(LED_BUILTIN, LOW); // turn the LED off by making the voltage LOW
}

void loop() {


  int currentState = digitalRead(inputPin); // Read the Nayax signal

  // Check if the state has changed from LOW to HIGH
  if (currentState == HIGH && lastState == LOW) {
    count++;
    Serial.print("Pulse: ");
    Serial.println(count);
    digitalWrite(LED_BUILTIN, HIGH); // turn the LED on (HIGH is the voltage level)
    Keyboard.press(0x20);           // press space
    delay(100);
    Keyboard.releaseAll();          // Release the key
    delay(1000);                   // Debounce delay to prevent multiple triggers
    digitalWrite(LED_BUILTIN, LOW); // turn the LED off by making the voltage LOW
  }
}
```

```
lastState = currentState; // Update the last state  
}
```

Aansluitschema

image not found or type unknown



Arduino 5v - Optocoupler +
Arduino GRND - weerstand 10K - pin12
Arduino Pin 12 - GRND Optocoupler
Optocoupler primair 12 volt via 10K weerstand

Pin 12 wordt met een pull down weerstand laag (0) gehouden. De (1) is 5V wordt via de optocoupler verbonden aan pin12 als er een signaal via de optocoupler binnenkomt. De stroom die door de 10K weerstand loopt als de optocoupler 'aan' staat, is 0.5 mA (2.5 mW).

De 10K weerstand voor de 12v primaire kant v/d optocoupler is proefondervindelijk vastgesteld. Bij 12v en 10K weerstand staat er 5v op de primare ingang en werkt de optocoupler goed. Meer spanning (lager weerstand kan) volgens de specs maar is onnodig.

Explanation primary side optocoupler

Since the pulse goes **low (0V)** when active and you want the LED to **turn on**, we need to connect the pulse wire to the cathode (Pin 2) and supply a positive voltage to the anode (Pin 1) through a current-limiting resistor. When the pulse pulls low, it completes the circuit, allowing current to flow through the LED. When floating, a pull-up resistor ensures the LED stays off.

Primary (Input) Side: Connecting to Nayax

1. Calculate the Current-Limiting Resistor:
 - LED forward voltage (V_F): $\sim 1.4V$.
 - Desired LED current (I_F): 10mA (0.01A).
 - Voltage drop across the resistor: $24V - 1.4V = 22.6V$.
 - Resistor value: $R = 22.6V / 0.01A = 2260\Omega \rightarrow$ Use a **2.2k Ω** resistor.
2. Add a Pull-Up Resistor:

- When the pulse wire floats (inactive), we need the LED off. A pull-up resistor on the cathode (Pin 2) to +24V ensures no current flows when the wire is floating.
- Use a **10kΩ pull-up resistor**. This keeps the cathode at 24V when floating, preventing current through the LED.

3. Wiring the Primary Side:

- +24V Supply: Connect to one end of the 2.2kΩ resistor.
- 2.2kΩ Resistor to Pin 1 (Anode): Connect the other end to Pin 1 of the PC817.
- Pin 2 (Cathode): Connect to the green Pulse 1 wire and one end of the 10kΩ pull-up resistor.
- 10kΩ Pull-Up Resistor: Connect the other end to +24V.
- Nayax Ground: Ensure the 24V supply ground is the same as the Nayax ground.
- Behavior:
 - Inactive (Floating): The 10kΩ pull-up keeps Pin 2 at 24V, same as Pin 1's effective voltage (24V - 1.4V drop across resistor), so no current flows (LED off).
 - Active (Low, 0V): The pulse wire pulls Pin 2 to ground, creating a 22.6V drop across the resistor and LED, driving ~10mA through the LED (on).

Explanation of Behavior

- **Inactive (Floating):** The pull-up resistor ties Pin 2 to 24V. Pin 1 is at ~22.6V (24V minus the resistor drop if any current flowed), but since Pin 2 is also at 24V, there's no voltage difference across the LED—no current, no light.
- **Active (Low, 0V):** The Nayax pulls the green wire (Pin 2) to ground. Now, Pin 1 is at 24V through the resistor, and Pin 2 is at 0V. The LED sees ~1.4V, the resistor drops the remaining 22.6V, and ~10mA flows—LED turns on.

Sets and availability

Step 1

Reformat *plannedequipment* into *reservations per date*

Processes equipment reservation data.

- Reads **reservation** records from JSON files in the "**plannedequipment**" directory.
- Reads **equipment properties** from JSON files in the "**equipment**" directory.

Calculates daily reservation totals for each equipment item.

- Covers a date range: current month plus a configurable number of months (default 9).
- Organizes data into a nested structure: year → month → day.

Computes daily available quantity: current quantity minus reservations.

Outputs results to JSON files in the "**reservationperdate**" directory.

Offers optional features:

- Suppression of days with zero reservations.
- Prevention of file creation when no reservation data exists.

Script

```
# createReservationperdatev2.py

import os
import json
from datetime import datetime, date, timedelta
import calendar

# Parameters
SUPPRESS_ZERO = True          # If True, skip storing day nodes with zero reservations.
```

```

SUPPRESS_EMPTY_FILE = True    # If True, do not create an output file if the "dates" part is empty.
ADDITIONAL_MONTHS = 9        # Number of additional months to process (beyond the current month)

# Define the directories
plannedequipment_dir = 'plannedequipment'
equipment_dir = 'equipment'
output_dir = 'reservationperdate'
os.makedirs(output_dir, exist_ok=True)

# Define the date range: from the first day of this month to the last day of the month ADDITIONAL_MONTHS
later.
today = date.today()
start_date = date(today.year, today.month, 1)
end_month = today.month + ADDITIONAL_MONTHS
end_year = today.year + (end_month - 1) // 12
end_month = ((end_month - 1) % 12) + 1
last_day = calendar.monthrange(end_year, end_month)[1]
end_date = date(end_year, end_month, last_day)

# Define the list of equipment property keys to copy from the equipment JSON files.
equipment_keys = ["is_combination", "is_physical", "current_quantity"]

def add_day(nested_dates, current_date):
    """Ensure that nested_dates[year][month][day] exists and initialize it."""
    year = str(current_date.year)
    month = f"{current_date.month:02d}"
    day = f"{current_date.day:02d}"

    if year not in nested_dates:
        nested_dates[year] = {}
    if month not in nested_dates[year]:
        nested_dates[year][month] = {}
    if day not in nested_dates[year][month]:
        nested_dates[year][month][day] = {"reservations": 0, "available": None}

def remove_empty_containers(nested_dates):
    """Remove empty month and year nodes if they have no day entries."""
    years_to_remove = []
    for year, months in nested_dates.items():

```

```

months_to_remove = []
for month, days in months.items():
    if not days: # If month dictionary is empty
        months_to_remove.append(month)
for month in months_to_remove:
    del nested_dates[year][month]
if not nested_dates[year]:
    years_to_remove.append(year)
for year in years_to_remove:
    del nested_dates[year]

# Process each JSON file in the plannedequipment directory.
for filename in os.listdir(plannedequipment_dir):
    if not filename.endswith('.json'):
        continue

    # Build full paths for plannedequipment, equipment and output files.
    plan_file_path = os.path.join(plannedequipment_dir, filename)
    equipment_file_path = os.path.join(equipment_dir, filename)
    output_path = os.path.join(output_dir, filename)

    # Load the reservation data from the plannedequipment file.
    with open(plan_file_path, 'r', encoding='utf-8') as infile:
        plan_data = json.load(infile)

    # Initialize the nested dates dictionary.
    nested_dates = {}
    current_date = start_date
    while current_date <= end_date:
        add_day(nested_dates, current_date)
        current_date += timedelta(days=1)

    # Process each reservation record.
    for record in plan_data.get('data', []):
        start_str = record.get('planperiod_start')
        end_str = record.get('planperiod_end')
        if not start_str or not end_str:
            continue

```

```

record_start = datetime.fromisoformat(start_str).date()
record_end = datetime.fromisoformat(end_str).date()
# Clamp the reservation period to our target range.
period_start = max(record_start, start_date)
period_end = min(record_end, end_date)
if period_start > period_end:
    continue

quantity = record.get('quantity', 0)
current = period_start
while current <= period_end:
    year = str(current.year)
    month = f"{current.month:02d}"
    day = f"{current.day:02d}"
    if year in nested_dates and month in nested_dates[year] and day in nested_dates[year][month]:
        nested_dates[year][month][day]["reservations"] += quantity
    current += timedelta(days=1)

# Initialize equipment properties.
item_properties = {}
current_quantity = 0

# Read the corresponding equipment file.
if os.path.exists(equipment_file_path):
    with open(equipment_file_path, 'r', encoding='utf-8') as eq_file:
        equipment_data = json.load(eq_file)
    equipment_item = equipment_data.get('data', {})
    # Copy the desired properties.
    for key in equipment_keys:
        item_properties[key] = equipment_item.get(key, None)
    current_quantity = equipment_item.get('current_quantity', 0)
else:
    print(f"Error: Equipment file '{filename}' not found in '{equipment_dir}'. Assuming current_quantity = 0
and default item properties.")
    for key in equipment_keys:
        item_properties[key] = None

# Update each day with the available quantity and optionally suppress days with zero reservations.
for year in list(nested_dates.keys()):

```



```

for month in list(nested_dates[year].keys()):
    for day in list(nested_dates[year][month].keys()):
        day_data = nested_dates[year][month][day]
        reservations = day_data["reservations"]
        day_data["available"] = current_quantity - reservations
        if SUPPRESS_ZERO and reservations == 0:
            del nested_dates[year][month][day]
    # If a month becomes empty after removing days, remove the month.
    if not nested_dates[year][month]:
        del nested_dates[year][month]
# If a year becomes empty after removing months, remove the year.
if not nested_dates[year]:
    del nested_dates[year]

# If SUPPRESS_EMPTY_FILE is True and the nested dates dictionary is empty,
# remove the output file if it exists and skip writing.
if SUPPRESS_EMPTY_FILE and not nested_dates:
    if os.path.exists(output_path):
        os.remove(output_path)
        print(f"Removed existing file {output_path} because there are no reservations.")
    continue

# Combine the item properties and the nested date reservation data.
output_data = {
    "item": item_properties,
    "dates": nested_dates
}

# Write the result to the output directory.
with open(output_path, 'w', encoding='utf-8') as outfile:
    json.dump(output_data, outfile, indent=2)

print("Reservation, availability, and item data have been processed and saved.")

```

Step 2

Download the set hierarchy from the API

(takes long, build in delays to prevent throttling)

```

# getSets.py

import json
import time
import requests
import sys

# Configuration variables (adjust these as needed)
BASE_URL = "https://api.rentman.net/" # Replace with your actual base URL

FILTER_ON_TAGS = False # Set to True if you want to apply tag filtering
API_TOKEN = "abc" # Replace with your actual API token

def log_message(message, force=False):
    """Logs a message. You can modify this to log to a file if needed."""
    sys.stderr.write(message + "\n")
    if force:
        print(message)

def count_api_usage():
    """Stub function for counting API usage."""
    # Extend this function to track API usage if needed.
    pass

def filter_array_by_selections(items, selections):
    """
    Filters an array of dictionaries based on the presence of certain keys with truthy values.

    :param items: List of dictionaries to filter.
    :param selections: List of keys to check.
    :return: Filtered list of dictionaries.
    """
    filtered = []
    for item in items:
        for sel in selections:
            if item.get(sel):
                filtered.append(item)
                break
    return filtered

```

```

def make_request(method, endpoint, data=None):
    """
    Makes an HTTP request using the requests library.

    :param method: HTTP method ('GET' or 'POST').
    :param endpoint: API endpoint (appended to BASE_URL).
    :param data: Dictionary of data or query parameters.
    :return: Parsed JSON response or None if error occurs.
    """
    if data is None:
        data = {}

    url = BASE_URL + endpoint
    headers = {
        "Authorization": f"Bearer {API_TOKEN}",
        "Content-Type": "application/json"
    }

    try:
        if method.upper() == 'POST':
            response = requests.post(url, headers=headers, json=data)
        elif method.upper() == 'GET':
            response = requests.get(url, headers=headers, params=data)
        else:
            log_message(f"Unsupported HTTP method: {method}")
            return None
    except requests.RequestException as e:
        log_message(f"Request exception: {e}")
        return None

    if not response.ok:
        log_message(f"HTTP error: {response.status_code} | Response Body: {response.text}")
    try:
        return response.json()
    except json.JSONDecodeError:
        log_message("Error decoding JSON response.")
        return None

```

```

def get_request(endpoint, params=None):
    """
    Performs a GET request and counts API usage.

    :param endpoint: API endpoint.
    :param params: Query parameters as a dictionary.
    :return: Parsed JSON response.
    """
    count_api_usage()
    return make_request('GET', endpoint, params)

def equipmentsetscontent(filter_on_tags=FILTER_ON_TAGS):
    """
    Retrieves equipment sets content by fetching data in batches.

    :param filter_on_tags: If True, applies tag filtering.
    :return: Complete list of items.
    """
    all_items = []
    offset = 0
    batch_size = 300
    total_fetched = 0

    while True:
        params = {'offset': offset, 'limit': batch_size}
        response = get_request('equipmentsetscontent', params)

        if not response or 'data' not in response:
            print("<pre><h1>Error in API Request</h1>")
            print(response)
            sys.exit(1)

        items = response['data']
        all_items.extend(items)
        total_fetched += len(items)

        # If fewer than batch_size items are returned, no more records are available.
        if len(items) < batch_size:
            break

```

```

offset += batch_size

# If 3000 records have been fetched, pause for 1 second to avoid rate limits.
if total_fetched >= 3000:
    log_message("Pausing for 1 second to avoid rate limits...", True)
    time.sleep(1)
    total_fetched = 0 # Reset the counter after the pause

if filter_on_tags:
    all_items = filter_array_by_selections(all_items, ['hoofditem', 'set'])

return all_items

# Main execution
if __name__ == "__main__":
    complete_data = equipmentsetscontent()
    print(json.dumps(complete_data, indent=4))

```

Step 3,

Convert the output from step 2 into sets-childs format (parent with list of childs).

For each entry, the script removes the "/equipment/" prefix from both the parent and child equipment values using the helper function.

For every entry, after stripping the prefixes, a new dictionary is created for the child item (containing the stripped child equipment and its quantity). This child dictionary is then appended to the list associated with the corresponding parent key in the dictionary.

Once all entries are processed, the dictionary keys (i.e., the parent equipment numbers) are sorted in ascending order to organize the final output.

Prompt

Write a Python script that performs the following tasks:

- Define variables at the top of the script for an input file and an output file. The input file is "sets/sets.json" and the output file is "sets/sets-childs.json".

- Read the JSON data from the input file. The file contains a list of objects, each with fields such as "parent_equipment", "equipment", and "quantity". The "parent_equipment" and "equipment" fields are strings that start with the prefix "/equipment/".
- Create a helper function to remove the "/equipment/" prefix from these strings.
- Group the objects by the numeric part of the parent equipment (after stripping the prefix). For each group, store a list of child items, where each child is represented by a dictionary containing the stripped "equipment" number and its "quantity".
- Sort the groups by their parent equipment keys in ascending numerical order.
- Write the resulting grouped and sorted data to the output file in JSON format with proper indentation.
- Please generate the complete Python code to achieve this.

```
# set-combined.py

import json
from collections import defaultdict

# Define file paths
input_file = "sets/sets.json"
output_file = "sets/sets-childs.json"

def strip_prefix(equipment_str):
    prefix = "/equipment/"
    return equipment_str[len(prefix):] if equipment_str.startswith(prefix) else equipment_str

# Load the input JSON file
with open(input_file, "r") as infile:
    data = json.load(infile)

# Group child items by parent equipment (after stripping the prefix)
sets_dict = defaultdict(list)
for entry in data:
    parent = strip_prefix(entry["parent_equipment"])
    child_item = {
        "equipment": strip_prefix(entry["equipment"]),
        "quantity": entry["quantity"]
    }
    sets_dict[parent].append(child_item)
```

```
# Sort the dictionary by parent keys in ascending numerical order
sorted_sets_dict = {k: sets_dict[k] for k in sorted(sets_dict.keys(), key=lambda x: int(x))}

# Write the output JSON file with sorted parent keys
with open(output_file, "w") as outfile:
    json.dump(sorted_sets_dict, outfile, indent=4)

print("The new JSON file has been created successfully.")
```

Step 4

Calculate set availability into reservationperdate-sets folder.

Prompt: [prompt to create set reservations.docx](#)

```
#!/usr/bin/env python3
# setReservationperdate.py

import os
import json
import math
from collections import defaultdict

# Directories for input and output files
SETS_FILE = os.path.join("sets", "sets-childs.json")
RESERVATION_DIR = "reservationperdate"
OUTPUT_DIR = "reservationperdate-sets"

# Ensure output directory exists
os.makedirs(OUTPUT_DIR, exist_ok=True)

def load_json(filepath):
    with open(filepath, "r") as f:
        return json.load(f)

def get_child_reservation(child_id):
```

```
"""
```

Given a child equipment id, load its reservation file.

Assumes filename is child_id + ".json" in the RESERVATION_DIR.

Returns a dict with keys "item" and optionally "dates".

```
"""
```

```
filepath = os.path.join(RESERVATION_DIR, f"{child_id}.json")
```

```
if os.path.exists(filepath):
```

```
    return load_json(filepath)
```

```
else:
```

```
    raise FileNotFoundError(f"Reservation file for equipment {child_id} not found at {filepath}")
```

```
def extract_date_availability(reservation):
```

```
    """
```

Extract a mapping from (year, month, day) tuple to available quantity.

If a reservation file has no "dates" node, returns an empty dict.

```
    """
```

```
    date_avail = {}
```

```
    dates = reservation.get("dates", {})
```

```
    for year, months in dates.items():
```

```
        for month, days in months.items():
```

```
            for day, data in days.items():
```

```
                date_avail[(year, month, day)] = data.get("available", 0)
```

```
    return date_avail
```

```
def nested_date_structure(date_dict):
```

```
    """
```

Given a mapping with keys (year, month, day) and value (availability),

build a nested dictionary: year -> month -> day -> {reservations: 0, available: value}

```
    """
```

```
    nested = defaultdict(lambda: defaultdict(dict))
```

```
    for (year, month, day), avail in date_dict.items():
```

```
        nested[year][month][day] = {"reservations": 0, "available": avail}
```

```
    return {year: dict(months) for year, months in nested.items()}
```

```
def main():
```

```
    # Load the sets definitions
```

```
    sets_def = load_json(SETS_FILE)
```

```
    # Process each set defined in sets-childs.json
```



```

for set_id, children in sets_def.items():
    child_infos = [] # List of tuples: (child_id, required_quantity, full_stock, date_availability mapping)
    for child in children:
        child_id = child["equipment"]
        req_qty = child["quantity"]
        try:
            reservation = get_child_reservation(child_id)
        except FileNotFoundError as e:
            print(e)
            continue # Skip this child if its reservation file is missing
        full_stock = reservation.get("item", {}).get("current_quantity", 0)
        date_avail = extract_date_availability(reservation)
        child_infos.append((child_id, req_qty, full_stock, date_avail))

# Calculate the full availability (without date restrictions)
available_sets_full = math.inf
for (_, req_qty, full_stock, _) in child_infos:
    child_full_sets = full_stock // req_qty
    available_sets_full = min(available_sets_full, child_full_sets)
if available_sets_full == math.inf:
    available_sets_full = 0

# Gather the union of all dates from the children
union_dates = set()
for (_, _, full_stock, date_avail) in child_infos:
    union_dates.update(date_avail.keys())

# Compute availability per date from the union of dates
date_results = {}
for date in union_dates:
    avail_for_date = math.inf
    for (_, req_qty, full_stock, date_avail) in child_infos:
        # Use date-specific available if provided, otherwise use full stock
        child_avail = date_avail.get(date, full_stock)
        child_sets = child_avail // req_qty
        avail_for_date = min(avail_for_date, child_sets)
    date_results[date] = avail_for_date

# Only include dates where the available set count is lower than full availability

```

```

filtered_dates = {date: avail for date, avail in date_results.items() if avail < available_sets_full}

# Build output JSON structure following the reservation file structure
output = {}
output["item"] = {
    "is_combination": True,
    "current_quantity": available_sets_full
}
if filtered_dates:
    output["dates"] = nested_date_structure(filtered_dates)

# Write the output JSON file for the set to the OUTPUT_DIR
out_filepath = os.path.join(OUTPUT_DIR, f"{set_id}.json")
with open(out_filepath, "w") as outfile:
    json.dump(output, outfile, indent=4)
print(f"Set {set_id}: full availability {available_sets_full} written to {out_filepath}")

if __name__ == "__main__":
    main()

```

Open issues

1. At the moment we only read and cache equipment belonging to a client. Set can consist out of items not belonging to any client directly, so there is no data available (in equipment). This means that there's no data for the availability in the cache. This would mean that we need to load and cache more equipment and more planned equipment.

These are approx. 1000 equipments (current number is 1200).

2. The calendar format for each month is:

```

Array ( [1] => 1 [2] => 1 [3] => 1 [4] => 1 [5] => 1 [6] => 1 [7] => 1 [8] => 1 [9] => 1 [10] =>
1 [11] => 1 [12] => 1 [13] => 1 [14] => 1 [15] => 1 [16] => 1 [17] => 1 [18] => 1 [19] => 1
[20] => 1 [21] => 1 [22] => 1 [23] => 1 [24] => 1 [25] => 1 [26] => 1 [27] => 1 [28] => 1 [29]
=> 1 [30] => 1 )

```

